

FAST & SECURE CLIP SYSTEM



INSTALLATION ON ANY SURFACE







ENGINEERED TIMBER FLOORING

Golden Elite's **Engineered Timber Flooring** is a more stable Timber flooring product that has a core which is composed of **multiple layers** of ply wood that are glued together, perpendicular to the grain.

There is a matte UV finish on each of the boards, on top of a 3mm or 4mm thick French Oak timber veneer that is effortless and straightforward to clean.

The **click system** makes installation quick and easy for both tradesmen and DIY projects.

Engineered timber looks and feels just like solid timber floors, but is more stable and economical due to it's composition. This helps keep out moisture and minimise expansion and contraction due to humidity and temperature, which in turn reinforces the durability of the boards.

Engineered timber can be sanded 1-2 times to **eliminate any scratches** and **blemishes** on the surface.

OUR COLOUR RANGE



AMERICAN
WALNUT
GELET14401
GELET15401

OAK
GELET14402
GELET15402

OAK
GELET14403
GELET15403

OAK
GELET14404
GELET15404

OAK
GELET14405
GELET15405

OAK
GELET14117
GELET15117

VINTAGE
GELET14118
GELET15118



SPECIFICATIONS

FRENCH OAK (AMERICAN WALNUT, TASMAN OAK, LIMED OAK, NATURAL OAK, LATTE OAK, SMOULDER OAK)			FRENCH OAK (HERRINGBONE VINTAGE)		
PLANK THICKNESS	15MM	14MM	PLANK THICKNESS	15MM	14MM
VENEER	4MM	3MM	VENEER	4MM	3MM
PLANK SIZE	1900 X 190		PLANK SIZE	600 X 120	
BOX	6 PCS		BOX	18 PCS	
AREA PER BOX	2.17M ²		AREA PER BOX	1.3M ²	

TECHNICAL DATA				
ТҮРЕ	ENGINEERED TIMBER			
COLOURS	7			
SUBSTRATE LAYER	ENGINEERED PLY WOOD CORE			
TOP LAYER	3MM OR 4MM TIMBER VENEER			
PROTECTIVE COATING	MATTE UV COATING			
INSTALLATION METHOD	CLICK SYSTEM			
SLIP TEST	R10			
FIRE TEST	MEAN CRITICAL RADIANT FLUX 2.3kW/M ² MEAN SMOKE DEVELOPMENT RATE 54%.MIN			







