

ENGINEERED BAMBOO

FAST & SECURE CLIP SYSTEM



INSTALLATION ON ANY SURFACE





Golden Elite's Engineered Bamboo Flooring is a **more stable** Bamboo flooring product that has a core which is composed of multiple layers of ply wood that are glued together, perpendicular to the grain.

There is a matte UV finish on each of the boards, on top of a 3mm thick natural bamboo veneer that is effortless and straightforward to clean.

The click system makes installation quick and easy for both tradesmen and DIY projects.

Engineered Bamboo looks and feels just like solid Bamboo floors, but is more stable and economical due to it's composition. This helps keep out moisture and minimise expansion and contraction due to humidity and temperature, which in turn reinforces the durability of the boards.

Engineered Bamboo can be sanded 1-2 times to eliminate any scratches and blemishes on the surface.



OUR COLOUR RANGE



















SPECIFICATIONS

ENGINEERED BAMBOO		
COLOUR	COFFEE, NATURAL, HONEY, TOFFEE, CHERRY, WHITE WASH, IVORY, MAHOGANY	
PLANK THICKNESS	14MM	
VENEER	3MM	
PLANK SIZE	1830MM X 190MM	
вох	6 PCS / 25% RANDOM LENGTH	
AREA PER BOX	2.09M ²	

TECHNICAL DATA		
ТҮРЕ	ENGINEERED BAMBOO	
SCRATCHING RESISTANCE	RATING 3	
PROTECTIVE COATING	13 LAYERS OF GERMAN POLYURETHANE COATING	
INSTALLATION METHOD	CLICK SYSTEM	
HARDNESS	10258N	
DENSITY	900KGS/M ³	
MOISTURE CONTENT	8-12%	
FORMALDEHYDE RATING	NATURAL BAMBOO VENEER: E0 NATURAL PLYWOOD BASE: E0 FLOORING GLUE: Non-poisonous	
SLIP TEST	R10 (AVERAGE 63)	
FIRE TEST	MEAN CRITICAL RADIANT FLUX 5.6Kw/M ² MEAN SMOKE DEVELOPMENT RATE 4%-MIN	
SURFACE BOND STRENGTH	1.91Mpa	
ABRASION RESISTANCE	WEAR INDEX I: 153 WEIGHT LOSS L: 153mg	







