



COLD PRESSED BAMBOO




Golden Elite Group


FAST & SECURE
CLIP SYSTEM



INSTALLATION
ON ANY SURFACE



NATURAL PATTERN



COLD PRESSED SOLID BAMBOO

Golden Elite's Cold Pressed Bamboo Range is available in 12mm and 14mm thick floor boards.

Cold Press Solid Bamboo is made by raw bamboo material being pressed into shape at room temperature. It is then baked for up to 20 hours at up to 130 degrees Celsius. The long baking time is slow and a great deal of dedication is used, resulting unrivalled density, colour and moisture content for a truly beautiful finish.

GE flooring proudly supplies premium quality Bamboo Flooring to residential and commercial clients across Australia at industry competitive prices.



GEBH1403 NATURAL



GEBH1401
COFFEE



GEBH1402
HONEY



12MM COLOUR RANGE



GEBH1202
SOHO

GEBM1204
OLIVE WOOD

GEBM1206
BLACK CHARCOAL

GEBM1207
COCOA BEANS

GEBM1208
BROWN ROAST

GEBM1209
IRON SILVER

GEBM1210
PINOT NOIR



14MM COLOUR RANGE



GEBH1401
COFFEE

GEBH1402
HONEY

GEBH1403
NATURAL

GEBH1404
MAHOGANY

GEBH1405
RICH BROWN

GEBH1407
GREY ASH OAK

GEBH1408
AMERICAN WALNUT

SPECIFICATIONS

12MM SOLID BAMBOO			14MM SOLID BAMBOO	
COLOUR	SOHO	OLIVE WOOD, BLACK CHARCOAL, COCOA BEANS, BROWN ROAST, IRON SILVER, PINOT NOIR	COLOUR	COFFEE, HONEY, NATURAL, MAHOGANY, RICH BROWN, GREY ASH OAK, AMERICAN WALNUT
PLANK THICKNESS	12MM		PLANK THICKNESS	14MM
PLANK SIZE	1820MM X 118MM	1850MM X 135MM	PLANK SIZE	1850MM X 135MM
BOX	9 PCS	8 PCS	BOX	6 PCS
AREA PER BOX	1.94M ²	2.0M ²	AREA PER BOX	1.50M ²

TECHNICAL DATA		
TYPE	COLD PRESS SOLID BAMBOO	
COLOURS	12MM : 7	14MM : 7
PROTECTIVE COATING	13 LAYERS OF GERMAN POLYURETHANE COATING	
INSTALLATION METHOD	CLICK SYSTEM	
HARDNESS	14+	
MOISTURE CONTENT	8-12%	
DENSITY	1050KGS/M ³	
FORMALDEHYDE RATING	E0	
SLIP TEST	R9	
FIRE TEST	MEAN CRITICAL RADIANT FLUX 5.6kW/M ² MEAN SMOKE DEVELOPMENT RATE 4%.MIN	



CONTACT US

(07) 3189 7117
 ADMIN@GOLDENELITEGROUP.COM.AU
 WWW.GOLDENELITEGROUP.COM.AU



Proud to be a Member of the

